

14-11-2017



EUCLID CHEMICAL

Kureseal

Water Based Curing & Sealing Membrane for Concrete



Advantages

- Ready mixed curing membrane and surface sealer.
- Ultra low odour.
- Good abrasion resistance.
- One coat spray application.
- Re-coatable with minimum preparation for certain types of coating.
- Extended service life over many commonly used coatings.

Product Description

Kureseal is a ultra low odour single pack white polymeric aqueous emulsion designed to impregnate concrete surfaces thus acting as a curing aid, surface sealer, dust-proofer and hardener.

Technical Data

Appearance	White emulsion, dries clear
Curing Efficiency	>75% at 6m ² /litre
Specific Gravity @ 15.6c	1.01 (approx.)
Flash Point (PMCC)	>100°C
Drying Time @ 20°C	Tack free—1-2 hours Hard dry—6-10 hours
Average Coverage (Emulsion)	5.5-6.6m ² /litre (approx)
Shelf Life (sealed)	12 months minimum
Compliance	ASTM C-309, Type1, Class A&B

Application

- Always stir or shake Kureseal before use.
- New Concrete: Apply using a fine spray at nominal consumption rate of 5-7m²/litre. Only one coat is required. Care should be taken to ensure full coverage is achieved.
- Old Concrete: Apply by Squeegee, brush or spray at a nominal consumption rate of 6-9m²/litre depending on surface porosity and texture.
- Never apply Kureseal in external situations where rain or frost is likely to come into contact with uncured material.
- All equipment should be cleaned with water.

Kureseal

Health & Safety

When working with Kureseal suitable protective clothing, eye/face protection and gloves should be worn.

For further health and safety information, please refer to the relevant Safety Data Sheet.

Packaging

Kureseal is available in 20 and 200 litre containers.

Storage

Kureseal should be stored under dry, frost-free conditions away from direct sunlight, under such conditions the shelf life is at least twelve months.

Important Notice

Whilst all reasonable care is taken in compiling technical data on the Company's products, all recommendations or suggestions regarding the use of such products are made without guarantee, since the conditions of use are beyond the control of the Company.

It is the responsibility of the customer to satisfy himself that each product is fit for the purpose for which he intends to use it, that the actual conditions of use are suitable, and that in the light of our continual research and development programme the information