

# Safety Data Sheet according to Regulation (EC) No. 2015/830

# SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

FLOWFAST RAPID TRANSIT **Revision Date:** 11/08/2017 **Product Identifier** 1.1

**SEALER** 

Supercedes Date: **New SDS** Flowfast Rapid Transit Sealer Product Name:

Relevant identified uses of the substance or mixture and uses

advised against

Coatings and paints, thinners, paint removers. Hand-mixing with intimate contact and only PPE available. Wide dispersive indoor use resulting in inclusion into or onto a matrix. For use by appropriately trained applicators. Roller application or brushing. Low energy spreading of coatings. Advised against: Home DIY applications, because of the health hazards and training required.

Details of the supplier of the safety data sheet 1.3

> Supplier: Flowcrete UK Ltd.

The Flooring Technology Centre

Booth Lane

Moston, Sandbach, Cheshire. UK

CW11 3QF

Tel: +44 (0)1270 753000 Fax: +44 (0)1270 753333 ehs.uk@flowcrete.com http://www.flowcrete.co.uk

ehs.uk@flowcrete.com **Datasheet Produced by:** 

CHEMTREC +001 703 5273887 (Outside US) 1.4 Emergency telephone number: CHEMTREC 1-800-424-9300 (Inside US)

# **SECTION 2: Hazard Identification**

#### 2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

### HAZARD STATEMENTS

| Flammable Liquid, category 2           | H225 |
|--|------|
| Skin Irritation, category 2            | H315 |
| Skin Sensitizer, category 1            | H317 |
| Serious Eye Damage, category 1         | H318 |
| STOT, single exposure, category 3, RTI | H335 |

Label elements

# Symbol(s) of Product



### Signal Word

Danger

2.2

### Named Chemicals on Label

Methyl methacrylate, N,N-bis-(2-Hydroxyethyl)-p-toluidine

### **HAZARD STATEMENTS**

| Flammable Liquid, category 2           | H225         | Highly flammable liquid and vapour.   |
|--|--------------|---|
| Skin Irritation, category 2            | H315         | Causes skin irritation.   |
| Skin Sensitizer, category 1            | H317         | May cause an allergic skin reaction.  |
| Serious Eye Damage, category 1         | H318         | Causes serious eye damage.  |
| STOT, single exposure, category 3, RTI | H335         | May cause respiratory irritation.   |
| PRECAUTION PHRASES                     |              |   |
|  | P210         | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                      |
|  | P235         | Keep cool.  |
|  | P261         | Avoid breathing dust/fume/gas/mist/vapours/spray.   |
|  | P280         | Wear protective gloves/protective clothing/eye protection/<br>face protection.  |
|  | P301+310     | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.   |
|  | P302+352     | IF ON SKIN: Wash with plenty of soap and water.   |
|  | P304+340     | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                    |
|  | P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. |
|  | P333+313     | If skin irritation or rash occurs: Get medical advice/attention.  |

closed.

Store in a well-ventilated place. Keep container tightly

#### Other hazards 2.3

No Information

### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

P403+233

# **SECTION 3: Composition/Information On Ingredients**

### 3.2 **Mixtures**

### **Hazardous Ingredients**

| <u>CAS-No.</u> | EINEC No. | Name According to EEC                | <u>%</u> |
|----------------|-----------|--------------------------------------|----------|
| 80-62-6        | 201-297-1 | Methyl methacrylate                  | 25-50    |
| 103671-44-9    | 600-470-2 | N,N-bis-(2-Hydroxyethyl)-p-toluidine | 2.5-10   |

CAS-No. REACH Reg No. **CLP Symbols CLP Hazard Statements** M-Factors 80-62-6 01-2119452498-28 GHS02-GHS07 H225-315-317-335

103671-44-9 **GHS05-GHS07** H302-318

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

Product: FLOWFAST RAPID TRANSIT SEALER

# **SECTION 4: First-aid Measures**

Date Printed: 11/08/2017

### 4.1 Description of First Aid Measures

**GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance. Remove contaminated clothing and shoes.

**AFTER INHALATION:** Keep respiratory tract clear. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do NOT use solvents or thinners.

AFTER EYE CONTACT: Keep eye wide open while rinsing. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. If symptoms persist, call a physician or Poison Control Centre immediately. Never give anything by mouth to an unconscious person. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

No Information

### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# **SECTION 5: Fire-fighting Measures**

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

### 5.2 Special hazards arising from the substance or mixture

Explosive reaction may occur on heating or burning. In use, may form flammable/explosive vapour-air mixture.

### 5.3 Advice for firefighters

Keep containers and surroundings cool with water spray. Fire will produce dense black smoke containing hazardous combustion products (see section 10). Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### **SECTION 6: Accidental Release Measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak. Remove all sources of ignition.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Ventilate the area. Refer to protective measures listed in sections 7 and 8.

### 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

# **SECTION 7: Handling and Storage**

### 7.1 Precautions for safe handling

Take measures to prevent the build up of electrostatic charge. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Provide exhaust

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good industrial hygiene and safety practice. Keep working clothes separately. Keep away from food, drink and animal feeding stuffs. When using, do not eat, drink or smoke. Wash hands and face before breaks and immediately after handling the product.

### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Heat, flames and sparks.

**STORAGE CONDITIONS:** Store at room temperature in the original container. Keep in an area equipped with solvent resistant flooring. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

### 7.3 Specific end use(s)

Used with Flowfast catalyst. Component of a resin flooring product. The mixing and application to be in accordance with the technical data sheets.

# **SECTION 8: Exposure Controls/Personal Protection**

### 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (UK WELS)

| <u>Name</u>                          | CAS-No.     | LTEL ppm | STEL ppm | STEL mg/m3 | LTEL mg/m3 |
|--------------------------------------|-------------|----------|----------|------------|------------|
| Methyl methacrylate                  | 80-62-6     | 50       | 100      | 416        | 208        |
| N.N-bis-(2-Hydroxyethyl)-p-toluidine | 103671-44-9 |          |          |            |            |

Name CAS-No. OEL Note

Methyl methacrylate 80-62-6

N,N-bis-(2-Hydroxyethyl)-p-toluidine 103671-44-9

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

### 8.2 Exposure controls

### **Personal Protection**

**RESPIRATORY PROTECTION:** Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. In case of insufficient ventilation wear suitable respiratory equipment. Respirator with filter for organic vapor. **EYE PROTECTION:** Eye wash bottle with pure water. Safety goggles. Safety glasses with side-shields conforming to EN166.

**HAND PROTECTION:** Solvent-resistant gloves. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Protective suit. Remove contaminated clothing and protective equipment before entering eating areas.

### **OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** As a rule, at least 10 air changes per hour are recommended at the workplace. Avoid contact with skin, eyes and clothing. Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

**Chemical Name:** Methyl methacrylate

EC No.: CAS-No.: 201-297-1 80-62-6

### **DNELs - Derived no effect level**

|            | Workers      |                        |                        | Consumers             |                        |               |                        |                        |
|------------|--------------|------------------------|------------------------|-----------------------|------------------------|---------------|------------------------|------------------------|
| Route of   | Acute effect | Acute effects          | Chronic                | Chronic effects       | Acute effect           | Acute effects | Chronic                | Chronic effects        |
| Exposure   | local        | systemic               | effects local          | systemic              | local                  | systemic      | effects local          | systemic               |
| Oral       |              | Not                    | required               |                       |                        | · •           |                        |                        |
| Inhalation |              |                        | 208 mg/m <sup>3</sup>  | 208 mg/m <sup>3</sup> |                        |               | 104 mg/m <sup>3</sup>  | 74.3 mg/m <sup>3</sup> |
| Dermal     |              | 1.5 mg/cm <sup>2</sup> | 1.5 mg/cm <sup>2</sup> | 13.67 mg/kg bw/       | 1.5 mg/cm <sup>2</sup> |               | 1.5 mg/cm <sup>2</sup> | 8.2 mg/kg bw/d         |
|            |              |                        | <u> </u>               | d                     |                        |               |                        |                        |

### PNEC's - Predicted no effect concentration

| Environmental protection target    | PNEC       |
|------------------------------------|------------|
| Fresh water                        | 0.94 mg/l  |
| Fresh water sediments              | 5.74 mg/kg |
| Marine water                       | 0.94 mg/l  |
| Marine sediments                   |            |
| Food chain                         |            |
| Microorganisms in sewage treatment |            |
| soil (agricultural)                | 1.47 mg/kg |
| Air                                |            |

# **SECTION 9: Physical and Chemical Properties**

9.1 Information on basic physical and chemical properties Appearance:

> **Physical State** Liquid

Odor strong MMA smell

Odor threshold 0.05 ppm

pН Not determined Melting point / freezing point (°C) Not determined Boiling point/range (°C) 101 - N.D.

Flash Point, (°C) 11

**Evaporation rate** Not determined Flammability (solid, gas) Not determined

Upper/lower flammability or explosive

limits

2.1 - 12.5

colourless

Vapour Pressure 38.7 mbar (MMA) Vapour density Not determined

Relative density 0.98

Solubility in / Miscibility with water Insoluble

Partition coefficient: n-octanol/water Not determined Auto-ignition temperature (°C) Not determined Decomposition temperature (°C) Not determined

Viscosity 130 - 170 mPa.s (25°C)

**Explosive properties** Not determined Oxidising properties Not determined Date Printed: 11/08/2017 Product: FLOWFAST RAPID TRANSIT SEALER

### 9.2 Other information

VOC Content g/l: <10

This is a calculated maximum VOC content for the mixed ready to use product (to Directive 2004/42/EC).

# **SECTION 10: Stability and Reactivity**

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions. Explosive reaction may occur on heating or burning.

# 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Polymerisation occurs when exposed to white light, ultraviolet light or heat.

### 10.4 Conditions to avoid

Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Heat, flames and sparks.

### 10.5 Incompatible materials

Oxidizing agents. Amines. Reducing agents. Heavy metal salts. Avoid radical-forming starting agents, peroxides and reactive metals.

### 10.6 Hazardous decomposition products

In case of fire **hazardous decomposition products** may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). No dangerous reaction known under conditions of normal use.

# **SECTION 11: Toxicological Information**

### 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: No Information Inhalation LC50: No Information

Irritation: Skin Irritation, category 2

Corrosivity: No information available.

Sensitization: Prolonged or repeated skin contact may result in allergic eczema.

Repeated dose toxicity: No information available.

Carcinogenicity: Non-carcinogenic in inhalation and feeding studies carried out on rats, mice, and dogs.

Source: Reference literature for methyl methacrylate.

Mutagenicity: Not mutagenic according to internationally accepted criteria. Source: Reference literature

(methly methacrylate).

**Toxicity for reproduction:** No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

Date Printed: 11/08/2017 Product: FLOWFAST RAPID TRANSIT SEALER

Oral LD50 CAS-No. Name According to EEC **Dermal LD50** Vapor LC50 80-62-6 Methyl methacrylate 7872 mg/kg (rat) >5000 mg/kg (rabbit) 3750 ppm (rat)

### Additional Information:

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons.

# **SECTION 12: Ecological Information**

12.1 Toxicity:

EC50 48hr (Daphnia): No information IC50 72hr (Algae): No information LC50 96hr (fish): No information

MMA: 94 %, OECD 301 C. 12.2 Persistence and degradability:

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

Other adverse effects: No information

CAS-No. Name According to EEC EC50 48hr IC50 72hr LC50 96hr

80-62-6 Methyl methacrylate 69 mg/l (OECD 202) >110 mg/l 79 mg/l (OECD 203) 103671-44-9 N,N-bis-(2-Hydroxyethyl)-p-toluidine No information No information No information

# **SECTION 13: Disposal Considerations**

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. Dispose of as hazardous waste in compliance with local and national regulations. Container hazardous when empty. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

**European Waste Code:** 080111\* 150110 Packaging Waste Code:

# **SECTION 14: Transport Information**

**UN number** 1866

14.2 UN proper shipping name Resin solution

(methyl methacrylate) **Technical name** 

14.3 Transport hazard class(es)

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards Not applicable 14.6 Special precautions for user Not applicable EmS-No.: F-E, S-E

14.7 Transport in bulk according to Annex II

of MARPOL 73/78 and the IBC code

Not applicable

# **SECTION 15: Regulatory Information**

Safety, health and environmental regulations/legislation for the substance or mixture:

**National Regulations:** 

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

WGK Class:

Covered by Directive 2012/18/EC (Seveso III): Not applicable

Restrictions to product or to substances according

to Annex XVII, Regulation (CE) 1907/2006: Not applicable

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### SECTION 16: Other Information

### Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

| H225 | Highly flammable liquid and vapour. |
|------|-------------------------------------|
|------|-------------------------------------|

H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

### Reasons for revision

new SDS - KmB 11th August 2017

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit

Date Printed: 11/08/2017 Product: FLOWFAST RAPID TRANSIT SEALER

OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter

TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.