



Safety Data Sheet according to Regulation (EC) 'No. 2015/830

SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier	HYDRASEAL DPM HARDENER B	Revision Date:	29/04/2021
Product Name:	Hydraseal DPM Hardener B	Supersedes Date:	27/01/2021

UFI Code: K081-Q0Q8-000C-40SS

1.2 Relevant identified uses of the substance or mixture and uses advised against	Coatings and paints, thinners, paint removers. Manual activities involving hand contact. Widespread use leading to inclusion into/onto article (indoor). For use by appropriately trained applicators. Roller application or brushing. Low energy spreading of coatings. Advised against: Home DIY applications, because of the health hazards and training required.
--	---

1.3 Details of the supplier of the safety data sheet

Manufacturer: Flowcrete Polska Sp. z o. o.
Ul. Marywilska 34
03-228 Warszawa
Polska

Tel: +48 22 879 8907
Fax: +48 22 879 8918
ehs.uk@flowcrete.com
www.flowcrete.com.pl/

Datasheet Produced by: ehs.uk@flowcrete.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)

Giftinformasjonen: +47 22 59 13 00

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Skin Corrosion, category 1B	H314-1B
Skin Sensitizer, category 1	H317
Respiratory Sensitizer, category 1	H334
Reproductive_ToxicityF_category_2	H361f
Hazardous to the aquatic environment, Chronic, category 2	H411

2.2 Label elements**Symbol(s) of Product****Signal Word**

Danger

Named Chemicals on Label

4-tert-Butylphenol, Ethylenediamine, m-Phenylenebis(methylamine), Trimethylhexane-1,6-diamine

HAZARD STATEMENTS

Skin Corrosion, category 1B	H314-1B	Causes severe skin burns and eye damage.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Respiratory Sensitizer, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Reproductive_ToxicityF_category_2	H361f	Suspected of damaging fertility.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P285	In case of inadequate ventilation wear respiratory protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P341	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342+311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

SECTION 3: Composition/Information On Ingredients**3.2 Mixtures****Hazardous ingredients**

<u>Name According to EEC</u>	<u>EINEC No.</u>	<u>CAS-No.</u>	<u>%</u>	<u>Classifications</u>	
4-tert-Butylphenol	202-679-0	98-54-4	2.5 - <10	H315-318-361F-410	Aquatic Chronic 1, Eye Dam. 1, Repr. 2, Skin Irrit. 2
m-Phenylenebis (methylamine)	216-032-5	1477-55-0	2.5 - <10	H302-314-317-332-412	Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1
Trimethylhexane-1,6-diamine	247-134-8	25620-58-0	1.0 - <2.5	H302-314-317-412	Acute Tox. 4 Oral, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1
Ethylenediamine	203-468-6	107-15-3	1.0 - <2.5	H226-302-311-314-317-332-334-412	Acute Tox. 3 Dermal, Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Aquatic Chronic 3, Flam. Liq. 3, Resp. Sens. 1, Skin Corr. 1B, Skin Sens. 1

<u>CAS-No.</u>	<u>M-Factors</u>	<u>REACH Reg No.</u>
98-54-4	1	01-2119489419-21
1477-55-0		01-2119480150-50
25620-58-0		01-2119560598-25
107-15-3		01-2119480383-37

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures**4.1 Description of First Aid Measures**

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance. Risk of product entering the lungs on vomiting after ingestion. Remove contaminated clothing and shoes.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure. Keep respiratory tract clear.

Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Keep eye wide open while rinsing. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. If swallowed, seek medical advice immediately and show this container or label.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Keep containers and surroundings cool with water spray. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Fire will produce dense black smoke containing hazardous combustion products (see section 10). In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Refer to protective measures listed in sections 7 and 8.

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Use only in well-ventilated areas. Do not breathe vapours or spray mist.

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good

industrial hygiene and safety practice. Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Wash hands and face before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Do not freeze. Direct sources of heat.

STORAGE CONDITIONS: Do not freeze. Store in original container. Store at room temperature in the original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

Component of a resin flooring product. The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
4-tert-Butylphenol	98-54-4				
m-Phenylenebis(methylamine)	1477-55-0				
Trimethylhexane-1,6-diamine	25620-58-0				
Ethylenediamine	107-15-3				

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
4-tert-Butylphenol	98-54-4	
m-Phenylenebis(methylamine)	1477-55-0	
Trimethylhexane-1,6-diamine	25620-58-0	
Ethylenediamine	107-15-3	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In case of insufficient ventilation wear suitable respiratory equipment. Respirator with filter for organic vapor.

EYE PROTECTION: Eye wash bottle with pure water. Tightly fitting safety goggles. Face-shield.

HAND PROTECTION: Impervious gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: As a rule, at least 5 air changes per hour are recommended at the workplace. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Chemical Name:

4-tert-Butylphenol

EC No.:

202-679-0

CAS-No.:

98-54-4

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							0.026 mg/kg
Inhalation				0.5 mg/m ³				0.09 mg/m ³
Dermal				0.071 mg/kg				0.026 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.01 mg/l
Fresh water sediments	0.975 mg/kg
Marine water	0.001 mg/l
Marine sediments	0.0975 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	1.5 mg/l
Air	0.324 mg/kg

Chemical Name:

m-Phenylenebis(methylamine)

EC No.:

216-032-5

CAS-No.:

1477-55-0

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							
Inhalation			0.2 mg/m ³	1.2 mg/m ³				
Dermal				0.33 mg/kg bw/d				

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.094 mg/l
Fresh water sediments	0.43 mg/kg
Marine water	0.0094 mg/l
Marine sediments	0.043 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	10 mg/l
Air	0.045 mg/kg

Chemical Name:

Trimethylhexane-1,6-diamine

EC No.:

247-134-8

CAS-No.:

25620-58-0

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							
Inhalation								
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.102 mg/l
Fresh water sediments	0.662 mg/kg
Marine water	0.01 mg/l
Marine sediments	0.062 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	72 mg/l
Air	

SECTION 9: Physical and Chemical Properties**9.1 Information on basic physical and chemical properties**

Appearance:	Amber
Physical State	Liquid
Odor	Amine like
Odor threshold	Not determined
pH	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	116 - N.D.
Flash Point, (°C)	>100
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	999 - 0
Vapour Pressure	Not determined
Vapour density	Not determined
Relative density	ca. 0.98
Solubility in / Miscibility with water	Insoluble
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Not determined
Explosive properties	Not determined

Oxidising properties	Not determined
-----------------------------	----------------

9.2 Other information

VOC Content g/l:	<10
-------------------------	-----

Specific Gravity (g/cm3)	0.120
---------------------------------	-------

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed. Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur. Hazardous polymerisation may occur.

10.4 Conditions to avoid

Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Do not freeze. Direct sources of heat.

10.5 Incompatible materials

Acids. Strong oxidizing agents.

10.6 Hazardous decomposition products

In case of fire **hazardous decomposition products** may be produced such as: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects**Acute Toxicity:**

Oral LD50:	No Information
-------------------	----------------

Inhalation LC50:	No Information
-------------------------	----------------

Irritation:

Irritating to eyes and skin. Vapour/spray mist may irritate respiratory system and lungs.

Corrosivity:

No information available.

Sensitization:

Prolonged or repeated skin contact may result in allergic eczema.

Repeated dose toxicity:

No information available.

Carcinogenicity:

No information available.

Mutagenicity:

No information available.

Toxicity for reproduction:

No information available.

STOT-single exposure:

No information available.

STOT-repeated exposure:

No information available.

Aspiration hazard:

No information available.

If no information is available above under **Acute Toxicity** then the acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
98-54-4	4-tert-Butylphenol	>2000 mg/kg	5600 mg/kg		0.000	0.000
1477-55-0	m-Phenylenebis(methylamine)	930 mg/kg (rat)	>2000 mg/kg (rabbit)	Not determined	Not determined	1.34 mg/l (rat)
25620-58-0	Trimethylhexane-1,6-diamine	910 mg/kg, oral, rat			0.000	0.000
107-15-3	Ethylenediamine	500 mg/kg (rat)	730 mg/kg (rat)		0.000	0.000

Additional Information:

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Corrosive - causes irreversible eye damage.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability:

No information

12.3 Bioaccumulative potential:

No information

12.4 Mobility in soil:

No information

12.5 Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects:

No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
98-54-4	4-tert-Butylphenol	3.4 to 4.5 mg/l	2.4 mg/l	4.71 to 5.62 mg/l
1477-55-0	m-Phenylenebis(methylamine)	15.2 mg/l (Daphnia magna)	20.3 mg/l (P. subcapitata)	87.6 mg/l (Oryzias latipes)
25620-58-0	Trimethylhexane-1,6-diamine	No information	29.5 mg/L	
107-15-3	Ethylenediamine	16.7 mg/L	645 mg/L	640 mg/L

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Dispose of as hazardous waste in compliance with local and national regulations. If recycling is not practicable, dispose of in compliance with local regulations. Container hazardous when empty. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

European Waste Code: 080111
Packaging Waste Code: 150110

SECTION 14: Transport Information

14.1	UN number	UN2735
14.2	UN proper shipping name	Amines, liquid, corrosive, N.O.S.
	Technical name	(m-Xylene diamine and Trimethylhexamethylenediamine)
14.3	Transport hazard class(es)	8
	Subsidiary shipping hazard	Not applicable
14.4	Packing group	III
14.5	Environmental hazards	Marine Pollutant
14.6	Special precautions for user	Not applicable
	EmS-No.:	Not applicable
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

SECTION 15: Regulatory Information**15.1 Safety, health and environmental regulations/legislation for the substance or mixture:****National Regulations:**

Denmark Product Registration Number:	Not available
Danish MAL Code:	3-5 (1993)
Danish MAL Code - Mixture:	Not available
Sweden Product Registration Number:	Not available
Norway Product Registration Number:	100100
Germany WGK Class:	2
Directive 2004/42/CE :	<10
Covered by Directive 2012/18/EC (Seveso III):	Not applicable
Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:	Not applicable

Annex XIV - Authorisation List:**CAS-No. Name According to EEC**

Not Applicable

SVHC - Substances of very high concern (Candidate List):**CAS-No. Name According to EEC**

98-54-4 4-tert-Butylphenol
107-15-3 Ethylenediamine

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H361f	Suspected of damaging fertility.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

Substance and/or Product Properties Changed in Section(s):

- 01 - Identification
- 02 - Hazard Identification
- 15 - Regulatory Information

Substance CAS Number Changed

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark;
 European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;
 European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP);
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m ³	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds

g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.