



## Declaration of Performance

According Annex III of the Regulation (EU) No 305/2011  
Amended by Commissions delegated Regulation (EU) No 574/2014

No: **FL-00001**

### For the system build-up: **Flowfast BC** consisting of:

**Primer:** Flowfast 101 Standard Primer, Flowfast 107 Ceramic-Metal Primer,  
Flowfast 108 Damp Primer, natural quartz

**Main layer:** Flowfast 205 Standard Binder+SNL Filler, colored quartz scatter

**Topcoat:** Flowfast 304 Standard Seal, Flowfast 305 Standard Seal LV or  
Flowfast 319 Flexible Seal

as described in our technical datasheets and application instruction guide.

1. Unique identification code of the product type:

**Flowfast BC**

2. Intended use/es:

**Synthetic resin screed for indoor use**

3. Manufacturer:

**Alteco Technik GmbH**  
**Raiffeisenstrasse 16, D-27239 Twistringen**  
**Germany**

4. System/s of AVCP

**System 4**  
**System 3 (Reaction to Fire)**

5. A) Harmonised standard

**EN13813:2002**

B) Notified body

CE **N/A**

UKCA **N/A**

6. Declared performance/s for **Flowfast BC**

Essential characteristics	Performance	Harmonized technical specification
Release of corrosive substances	SR	<b>EN 13813:2002</b>
Wear resistance	AR0.5	
Impact resistance	IR4	
Bond strength	B2.0	
Reaction to fire	C <sub>fl</sub> -s1	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with Regulation (Eu) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

**Maik Blohm**

At **Alteco Technik GmbH, Twistringen**

on **15.10.2021**

i.V.   
(authorised signature)

CE-marking

<b>CE</b>	
<b>Alteco Technik GmbH</b> <b>Raiffeisenstrasse 16, D-27239 Twistringen</b> <b>Germany</b>	
<b>13</b>	
<b>DoP no FL-00001</b>	
<b>EN 13813: 2002</b>	
Synthetic resin screed for indoor use	
Release of corrosive substances	SR
Abrasion resistance (BCA test)	AR0.5
Impact resistance	IR4
Bond strength	B2.0
Reaction to fire	C <sub>fi</sub> -s1

UKCA-marking

<b>UK CA</b>	
<b>Alteco Technik GmbH</b> <b>Raiffeisenstrasse 16, D-27239 Twistringen</b> <b>Germany</b>	
<b>21</b>	
<b>DoP no FL-00001</b>	
<b>EN 13813: 2002</b>	
Synthetic resin screed for indoor use	
Release of corrosive substances	SR
Abrasion resistance (BCA test)	AR0.5
Impact resistance	IR4
Bond strength	B2.0
Reaction to fire	C <sub>fi</sub> -s1