

## Declaration of Performance

According Annex III of the Regulation (EU) No 305/2011  
Amended by Commissions delegated Regulation (EU) No 574/2014

No: **H2019**

### For the product: **Matacryl Bitu-Primer**

as described in our technical datasheets and application instruction guide.

1. Unique identification code of the product type:

**Matacryl Bitu-Primer**

2. Intended use/es:

**Synthetic resin screed for indoor use**

3. Manufacturer:

**Alteco Technik GmbH  
Raiffeisenstrasse 16, D-27239 Twistringen  
Germany**

4. System/s of AVCP

**System 4**

5. A) Harmonised standard

**EN13813:2002**

B) Notified body

**not applicable**

6. Declared performance/s for **Matacryl Bitu-Primer**

The product is used in surface protection system  
of bridge decks:  
**Primer/Sealer for use under asphalt and bitumen  
based waterproofing systems**

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	$E_{fl}$	<b>EN 13813:2002</b>
Abrasion resistance	$\leq AR 0.5$	
Bond strength	$\geq B 2$	
Impact resistance	$\geq IR 4$	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

**Andreas Miller (Managing Director)**

At **Twistringen, Germany**

on **09.02.2021**

ppa   
(authorised signature)

<b>CE</b>	
<b>Alteco Technik GmbH</b> Raiffeisenstrasse 16, D-27239 Twistingen, Germany	
<b>14</b>	
<b>EN 13813: 2002</b>	
Synthetic resin screed for indoor use	
Reaction to fire	$E_{fl}$
Abrasion resistance	$\leq AR 0.5$
Bond strength	$\geq B 2$
Impact resistance	$\geq IR 4$

CE-marking

<b>UK CA</b>	
<b>Alteco Technik GmbH</b> Raiffeisenstrasse 16, D-27239 Twistingen, Germany	
<b>14</b>	
<b>EN 13813: 2002</b>	
Synthetic resin screed for indoor use	
Reaction to fire	$E_{fl}$
Abrasion resistance	$\leq AR 0.5$
Bond strength	$\geq B 2$
Impact resistance	$\geq IR 4$

UKCA-marking