Date Printed: 28/12/2022 Product: FLOWCOAT CR HARDENER

Safety Data Sheet according to Regulation (EC) 'No. 2020/878

















SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

FLOWCOAT CR HARDENER **Revision Date:** 28/12/2022 1.1 Product Identifier

Supersedes Date: 09/09/2021 **Product Name:** Flowcoat CR Hardener

UFI Code: K6D0-T0CD-E00X-RGYN

Nο Nanoform:

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Coatings and paints, thinners, paint removers. Manual activities involving hand contact. Widespread use leading to inclusion into/onto article (indoor). For use by appropriately trained applicators. Roller application or brushing. Low energy spreading of coatings. Advised against: Home DIY applications, because of the health hazards and training required. Advised against: others than recommended

Details of the supplier of the safety data sheet 1.3

> Tremco CPG Poland Sp. z o. o. Manufacturer:

UI. Marywilska 34 03-228 Warszawa

Polska

Tel: +48 22 879 8907 Fax: +48 22 879 8918 ehs.uk@flowcrete.com www.flowcrete.com.pl/

ehs.uk@flowcrete.com **Datasheet Produced by:**

CHEMTREC +1 703 5273887 (Outside US) 1.4 Emergency telephone number:

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Acute Toxicity, Oral, category 4	H302
Skin Corrosion, category 1B	H314-1B
Skin Sensitizer, category 1	H317
Acute Toxicity, Inhalation, category 4	H332
Reproductive_ToxicityF_category_1B	H360F
STOT, repeated exposure, category 2	H373
Hazardous to the aquatic environment, Chronic, category 3	H412

2.2 Label elements

Date Printed: 28/12/2022

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

4,4'-Isopropylidenediphenol, Benzyl alcohol, m-Phenylenebis(methylamine), Formaldehyde, polymer with benzenamine, hydrogenated

HAZARD STATEMENTS

Acute Toxicity, Oral, category 4	H302 H314-1B	Harmful if swallowed. Causes severe skin burns and eye damage.
Skin Corrosion, category 1B		, 3
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Reproductive_ToxicityF_category_1B	H360F	May damage fertility.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3 PRECAUTION PHRASES	H412	Harmful to aquatic life with long lasting effects.
Chronic, category 3	H373 H412	· ·

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P270	Do no eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention
P314	Get medical advice/attention if you feel unwell.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.

Date Printed: 28/12/2022

2.3 Other hazards
No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Name According to EEC CAS-No.

No Information

Endocrine disrupting properties - Ecotoxicity

Name According to EEC CAS-No.

No Information

SECTION 3: Composition/Information On Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous ingredients

Name According to EEC EINEC No. CAS-No. REACH Reg No.	<u>%</u>	Classifications	SCL Value: ATE Value: M-Factor:	
Benzyl alcohol 202-859-9 100-51-6	25 - <50	H302-319-332	SCL Value:	-
01-2119492630-38		Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Eye Irrit. 2	ATE Value: M-Factor:	-
Formaldehyde, polymer with benzenamine, hydrogenated 603-894-6	25 - <50	H302-314-317-373-412	SCL Value:	-
135108-88-2		Acute Tox. 4 Oral, Aquatic Chronic 3,	ATE Value:	-
01-2119983522-33		Skin Corr. 1C, Skin Sens. 1, STOT RE 2	M-Factor:	-

m-Phenylenebis(methylamine) 216-032-5	10 - <25	H302-314-317-332-412	SCL Value:	-
1477-55-0			ATE Value:	-
01-2119480150-50		Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1B	M-Factor:	-
4,4'-Isopropylidenediphenol	2.5 - <10	H317-318-335-360F	SCL Value:	-
80-05-7			ATE Value:	-
01-2119457856-23		Eye Dam. 1, Repr. 1B, Skin Sens. 1, STOT SE 3 RTI	M-Factor:	-

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance. Remove contaminated clothing and shoes.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure. Keep respiratory tract clear. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Keep eye wide open while rinsing. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Use water spray to cool unopened containers. Fire will produce dense black smoke containing hazardous combustion products

Date Printed: 28/12/2022

(see section 10). In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak.

6.1.2 For emergency responders

No Information

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Keep the container open.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). After cleaning, flush away traces with water. Refer to protective measures listed in sections 7 and 8.

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Do not breathe vapours or spray mist. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good industrial hygiene and safety practice. Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Wash hands and face before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Avoid dust accumulation in enclosed space. Do not freeze.

STORAGE CONDITIONS: Store in original container. Keep container tightly closed in a dry and well-ventilated place. Store at room temperature in the original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
Benzyl alcohol	100-51-6				

Benzyl alcohol 100-51-6 Formaldehyde, polymer with benzenamine, 135108-88-2

hydrogenated

m-Phenylenebis(methylamine) 1477-55-0

4,4'-lsopropylidenediphenol 80-05-7 2

CAS-No. OEL Note <u>Name</u>

Benzyl alcohol 100-51-6

Formaldehyde, polymer with 135108-88-2

benzenamine, hydrogenated m-Phenylenebis(methylamine)

Date Printed: 28/12/2022

1477-55-0

80-05-7

4,4'-Isopropylidenediphenol

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

Chemical Name:

Benzyl alcohol

EC No.: CAS-No.: 202-859-9 100-51-6

DNELs - Derived no effect level

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required			20 mg/kg bw/d 4 mg/kg bw/			
Inhalation	-	110 mg/m ³	-	22 mg/m ³	-	27 mg/m ³	-	5.4 mg/m ³
Dermal	-	40 mg/kg bw/d	-	8 mg/kg bw/d	-	20 mg/kg bw/d	-	4 mg/kg bw/d

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	1 mg/l
Fresh water sediments	5.27 mg/kg
Marine water	0.1 mg/l
Marine sediments	0.527 mg/kg
Food chain	
Microorganisms in sewage treatment	39 mg/l
soil (agricultural)	0.456 mg/kg
Air	

Chemical Name:

m-Phenylenebis(methylamine)

EC No.: CAS-No.: 216-032-5 1477-55-0

DNELs - Derived no effect level

	Workers					Con	sumers	
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required						
Inhalation	0.2 mg/m ³ 1.2 mg/m ³		1.2 mg/m ³					
Dermal	0.33 mg/kg bw/d							

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.094 mg/l
Fresh water sediments	0.43 mg/kg
Marine water	0.0094 mg/l
Marine sediments	0.043 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/l
soil (agricultural)	0.045 mg/kg
Air	

Date Printed: 28/12/2022 Product: FLOWCOAT CR HARDENER

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In case of insufficient ventilation wear suitable respiratory equipment. Respirator with a

EYE PROTECTION: Eye wash bottle with pure water. Safety goggles. Tightly fitting safety goggles. Safety glasses with side-shields conforming to EN 166.

HAND PROTECTION: Use chemical resistant gloves (EN 374): Nitrile rubber; thickness >= 0.5 mm; breakthrough time >= 480 min. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Remove contaminated clothing and protective equipment before entering eating areas.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: At temperatures below 40°C, provide a good standard of general ventilation (not less than 5 air changes per hour). At temperatures over 40°C - and always if sprayed - exhaust ventilation is required. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Colour: Yellow

Physical State Liquid Odor Mild

Odor threshold Not determined

Hq alkaline

Melting point / freezing point (°C) Not determined 205 - N.D.

Boiling point or initial boiling point and

boiling range (°C) Flash Point, (°C)

Not measured

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Llower and upper explosive limit Not determined

Vapour Pressure Not determined Relative vapour density Not determined

Density and/or relative density ~1.07

Solubility in / Miscibility with water Insoluble

Partition coefficient: n-octanol/water Not determined Auto-ignition temperature (°C) Not determined Decomposition temperature (°C) Not determined Kinematic viscosity Not determined

Particle characteristics Not applicable to liquids

9.2 Other information

VOC Content g/l: <200 Specific Gravity (g/cm3) 0.120

SECTION 10: Stability and Reactivity

10.1 Reactivity

Date Printed: 28/12/2022

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Container can be pressurized by carbon dioxide due to reaction with humid air and/or water. Stable under normal conditions.

10.3 Possibility of hazardous reactions

Polymerises at about 200°C with evolution of CO2. Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Avoid dust accumulation in enclosed space. Do not freeze.

10.5 Incompatible materials

Keep away from oxidising agents, strongly acid or alkaline materials, as well as of amines, alcohols and water. Amines and alcohols cause exothermic reactions.

10.6 Hazardous decomposition products

In case of fire **hazardous decomposition products** may be produced such as: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke. Preparation reacts slowly with water resulting in evolution of CO2. Evolution of CO2 in closed containers causes overpressure and produces a risk of bursting.

SECTION 11: Toxicological information

11.1 Information on hazard classes as definied in Regulation (EC) No 1272/2008

Acute Toxicity:

Oral LD50: No Information
Inhalation LC50: No Information
Dermal LD50: No Information

Irritation: No information available.

Corrosivity: Causes severe skin burns and eye damage.

Sensitization: May cause an allergic skin reaction.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: May damage fertility.

STOT-single exposure: No information available.

STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
100-51-6	Benzyl alcohol	1620 mg/kg (rat)	2001 mg/kg (rabbit)			> 4.178 mg/l (4 h, rat)
135108-88-2	Formaldehyde, polymer with benzenamine, hydrogenated	367 mg/kg, oral, rat	>2000			
1477-55-0	m-Phenylenebis (methylamine)		>2000 mg/kg (rabbit)	Not determined	Not determined	1.34 mg/l (rat)

Date Printed: 28/12/2022 Product: FLOWCOAT CR HARDENER

80-05-7 4,4'-Isopropylidenediphenol 5000 mg/kg (rat) 3600 mg/kg (rabbit) 0.000 0.000

Additional Information:

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. Isocyanates may cause acute irritation and/or sensitisation of the respiratory system leading to tightness of the chest, wheeziness and an asthmatic condition.

11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Name According to EEC CAS-No.

No Information

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB

assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Endocrine disrupting properties

Endocrine disrupting properties - Ecotoxicity

Name According to EEC CAS-No.

No Information

12.7 Other adverse effects:

No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
			770 "	400 # /D: 1 I
100-51-6	Benzyl alcohol	230 mg/l	770 mg/l (Pseudokirchneriella)	460 mg/l (Pimephales promelas)
135108-88-2	Formaldehyde, polymer with benzenamine, hydrogenated	No information	No information	
1477-55-0	m-Phenylenebis(methylamine)	15.2 mg/l (Daphnia magna)	20.3 mg/l (P. subcapitata)	87.6 mg/l (Oryzias latipes)
80-05-7	4,4'-Isopropylidenediphenol	No information	No information	

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: Dispose of as hazardous waste in compliance with local and national regulations. If recycling is not practicable, dispose of in compliance with local regulations. Container hazardous when empty. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

European Waste Code: 080111* **Packaging Waste Code:** 150110

SECTION 14: Transport Information

		ADR/RID	ADN	IMDG	IATA
14.1	UN-number	UN2735	UN2735	UN2735	UN2735
14.2	UN proper shipping name	Amines, liquid, corrosive, N.O.S., (Benzene-1,3- dimethaneamine (MXDA), mixed cycloaliphatic amines)	Amines, liquid, corrosive, N.O.S., (Benzene-1,3- dimethaneamine (MXDA), mixed cycloaliphatic amines)	Amines, liquid, corrosive, N.O.S., (Benzene-1,3- dimethaneamine (MXDA), mixed cycloaliphatic amines)	Amines, liquid, corrosive, N.O.S.,(Benzene-1,3- dimethaneamine (MXDA), mixed cycloaliphatic amines)
14.3	Transport Hazard Class(es)	8	8	8	8
14.4	Packing Group	III	III	III	III
14.5	Enviromental Hazards	No Information	No Information	No Information	No Information

14.6 Special precautions for user Not applicable
 EmS-No.: Not applicable
 14.7 Maritime transport in bulk according to IMO intruments

Not applicable

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number:

Date Printed: 28/12/2022 Product: FLOWCOAT CR HARDENER

Not available

Germany WGK Class: Not available

Directive 2004/42/CE : <200

Covered by Directive 2012/18/EC (Seveso III): Not applicable

Restrictions to product or to substances according

to Annex XVII, Regulation (CE) 1907/2006: Not applicable

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

80-05-7 4,4'-Isopropylidenediphenol

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H302	Harmful if swallowed.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H360F	May damage fertility.	
H373	May cause damage to organs through prolonged or repea	

May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Reasons for revision

Substance and/or Product Properties Changed in Section(s):

- 01 Identification
- 02 Hazard Identification
- 03 Composition/Information On Ingredients
- 08 Exposure Controls/Personal Protection
- 09 Physical and Chemical Properties
- 11 Toxicological Information
- 14 Transportation Information
- 15 Regulatory Information

Composition Information Changed

Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.

Product: FLOWCOAT CR HARDENER

Date Printed: 28/12/2022

- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments. - Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification of the product is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the exact composition of the formula

Acronym & Abbreviation Key:

Classification, Labeling & Packaging Regulation CLP

ЕC European Commission European Union ΕU United States US

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

Globally Harmonized System of Classification and Labeling of Chemicals GHS

Long term exposure limit LTEL. STEL Short term exposure limit Occupational exposure limit OEL

Parts per million ppm

Milligrams per cubic meter ma/m3 TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits VOC Volatile organic compounds

g/1Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

T₁C.5.0 Lethal concentration at 50%

EC50 Half maximal effective concentration Half maximal inhibitory concentration IC50 Persistent bioaccumulative toxic chemical PBT Very persistent and very bioaccumulative vPvB

European Economic Community EEC

International Transport of Dangerous Goods by Road ADR International Transport of Dangerous Goods by Rail RID

United Nations

International Maritime Dangerous Goods Code IMDG International Air Transport Association

International Convention for the Prevention of Pollution From Ships, 1973 as MARPOL

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NF. Narcotic Effects

TMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter \leq 10 μm .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.