Date Printed: 12/04/2023 Product: FLOWSEAL EPW GLOSSY PART A

# Safety Data Sheet according to Regulation (EC) 'No. 2020/878



















# SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

FLOWSEAL EPW GLOSSY PART A **Revision Date:** 12/04/2023 **Product Identifier** 

**Supersedes Date:** Flowseal EPW Glossy Part A New SDS **Product Name:** 

> 1 **Version Number:**

**UFI Code:** 3332-K0HX-300S-7SXD

Nanoform:

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Component of multicomponent coatings - Professional use only. Coatings and paints, thinners, paint removers. Manual activities involving hand contact. Widespread use leading to inclusion into/onto article (indoor). Widespread use leading to inclusion into/ onto article (outdoor). For use by appropriately trained applicators. Roller application or brushing. Advised against: Home DIY applications. Advised against: Spray application, because of the additional hazards. Advised against: others than

recommended

#### 1.3 Details of the supplier of the safety data sheet

Tremco CPG Poland Sp. z o. o. Manufacturer:

Ul. Marywilska 34 03-228 Warszawa

Polska

Tel: +48 22 879 8907 Fax: +48 22 879 8918 ehs.uk@flowcrete.com www.flowcrete.com.pl/

ehs.uk@flowcrete.com **Datasheet Produced by:** 

CHEMTREC +1 703 5273887 (Outside US) 1.4 Emergency telephone number:

# **SECTION 2: Hazards Identification**

#### 2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

**HAZARD STATEMENTS** 

# Other EU extensions EUH205 Skin Irritation, category 2 H315 Skin Sensitizer, category 1 H317 Eye Irritation, category 2 H319 Hazardous to the aquatic environment, Chronic, category 2 H411

#### 2.2 Label elements

#### Symbol(s) of Product





#### Signal Word

Warning

#### Named Chemicals on Label

bis[4-(2,3-epoxypropoxy))phenyl]propane, Formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane and phenol, 1,6-Hexanediol diglycidyl ether, Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

## **HAZARD STATEMENTS**

Other EU extensions	EUH205	Contains epoxy constituents. May produce an allergic reaction.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes.
		Remove contact lenses, if present and easy to do so.  Continue rinsing.
	P333+313 P391	If skin irritation or rash occurs: Get medical advice/attention. Collect spillage.

#### 2.3 Other hazards

Ingestion may cause irritation to mucous membranes.

#### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# **Endocrine disrupting properties - Toxicity**

Name According to EEC CAS-No.

No Information

**Endocrine disrupting properties - Ecotoxicity** 

Name According to EEC CAS-No.

No Information

# SECTION 3: Composition/Information On Ingredients

# 3.1 Substances

Not applicable

Date Printed: 12/04/2023

# 3.2 Mixtures

# Hazardous ingredients

Name According to EEC EINEC No. CAS-No. REACH Reg No.	<u>%</u>	Classifications	SCL Value: ATE Value: M-Factor:		
bis[4-(2,3-epoxypropoxy) phenyl]propane 216-823-5 1675-54-3 No Information	50 - <75	H315-317-319-411  Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1	SCL Value: ATE Value: M-Factor:	-	
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) 500-033-5 25068-38-6 01-2119456619-26	2.5 - <10	H315-317-319-411  Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1	SCL Value:  ATE Value:  M-Factor:	-	
1,6-Hexanediol diglycidyl ether 240-260-4 16096-31-4 01-2119463471-41	2.5 - <10	H315-317-319-412  Aquatic Chronic 3, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1	SCL Value:  ATE Value:  M-Factor:	-	

Propylene carbonate 203-572-1 108-32-7 01-2119537232-48	2.5 - <10	H319 Eye Irrit. 2	SCL Value:  ATE Value:  M-Factor:	-
Benzyl alcohol 202-859-9 100-51-6 01-2119492630-38	2.5 - <10	H302-319-332  Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Eye Irrit. 2	SCL Value:  ATE Value:  M-Factor:	-
Formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane and phenol 500-006-8 9003-36-5 01-2119454392-40	2.5 - <10	H315-317-411  Aquatic Chronic 2, Skin Irrit. 2, Skin Sens. 1	SCL Value:  ATE Value:  M-Factor:	-

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

## **SECTION 4: First-aid Measures**

Date Printed: 12/04/2023

# 4.1 Description of First Aid Measures

**GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Do not use solvent or thinners to clean skin. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** Consult a physician. Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

#### Self protection of the first aider:

Date Printed: 12/04/2023

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

May cause sensitization by skin contact. Irritating to eyes and skin.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# **SECTION 5: Firefighting Measures**

# 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Do not use a solid water stream as it may scatter and spread fire. Alcohol, Alcohol based solutions, any other media not listed above.

#### 5.2 Special hazards arising from the substance or mixture

In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

#### 5.3 Advice for firefighters

Keep containers and surroundings cool with water spray. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

## **SECTION 6: Accidental Release Measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Avoid contact with skin, eyes and clothing. For personal protection see section 8.2. Ensure adequate ventilation. Keep people away from and upwind of spill/leak.

## 6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

#### 6.2 Environmental precautions

Discharge into the environment must be avoided. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. May cause long-term adverse effects in the aquatic environment.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information. Refer to protective measures listed in sections 7 and 8.

#### **SECTION 7: Handling and Storage**

## 7.1 Precautions for safe handling

Wear personal protective equipment. Avoid contact with skin and eyes. Apply technical measures to comply with the occupational exposure limits (see section 8). People handling epoxy products must have received special training according to guidelines from the National Occupational Health and Safety Board.

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good industrial hygiene and safety practice. Keep working clothes separately. Keep away from food, drink and animal

feedingstuffs. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Do not freeze. STORAGE CONDITIONS: Keep out of the reach of children. Keep at temperatures between 10 and 25 °C. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Keep away from food, drink and animal feeding stuffs.

## 7.3 Specific end use(s)

Component of multicomponent coatings. The mixing and application to be in accordance with the technical data sheets.

# **SECTION 8: Exposure Controls/Personal Protection**

#### 8.1 Control parameters

and phenol

# Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	CAS-No.		LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
bis[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3					
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	25068-38-6					
1,6-Hexanediol diglycidyl ether	16096-31-4					
Propylene carbonate	108-32-7					
Benzyl alcohol	100-51-6					
Formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane and phenol						
<u>Name</u>	CAS-No.	OEL Note				
bis[4-(2,3-epoxypropoxy)phenyl]propane	1675-54-3					
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	25068-38-6					
1,6-Hexanediol diglycidyl ether	16096-31-4					
Propylene carbonate	108-32-7					
Benzyl alcohol	100-51-6					
Formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane	9003-36-5					

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

#### **Chemical Name:**

bis[4-(2,3-epoxypropoxy)phenyl]propane

**EC No.:** CAS-No.: 216-823-5 1675-54-3

# **DNELs - Derived no effect level**

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not required						
Inhalation				4.93 mg/m3				
Dermal				0.75 mg/kg bw/				
				day				

# PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.006 mg/l
Fresh water sediments	0.341 mg/kg
Marine water	0.001mg/l
Marine sediments	0.0341 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/l
soil (agricultural)	0.065 mg/kg
Air	

## **Chemical Name:**

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

**EC No.: CAS-No.:** 500-033-5 25068-38-6

## **DNELs - Derived no effect level**

	Workers			Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required				0.75 mg/kg		0.75 mg/kg	
Inhalation		12.25 mg/m <sup>3</sup>		12.25 mg/m <sup>3</sup>				
Dermal		8.33 mg/kg		8.33 mg/kg		3.571 mg/kg		3.571 mg/kg

# PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.006 mg/l
Fresh water sediments	0.996 mg/kg
Marine water	0.0006 mg/l
Marine sediments	0.0996 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/l
soil (agricultural)	0.196 mg/kg
Air	

**Chemical Name:** 1,6-Hexanediol diglycidyl ether

**EC No.: CAS-No.:** 240-260-4 16096-31-4

# DNELs - Derived no effect level

		Wo	orkers		Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required					0.83 mg/kg		0.83 mg/kg bw/d
						bw/d		
Inhalation			0.44 mg/m <sup>3</sup>	4.9 mg/m <sup>3</sup>		2.9 mg/m <sup>3</sup>	0.27 mg/m <sup>3</sup>	2.9 mg/m <sup>3</sup>
Dermal			22.6 μg/cm <sup>2</sup>	2.8 mg/kg bw/d	13.6 μg/cm <sup>2</sup>	1.7 mg/kg bw/	13.6 μg/cm <sup>2</sup>	1.7 mg/kg bw/d
						d	· -	

# PNEC's - Predicted no effect concentration

Environmental protection target	PNEC				
Fresh water	0.0115 mg/l				
Fresh water sediments	0.283 mg/kg				
Marine water	1.15 μg/l				
Marine sediments	0.283 mg/kg				
Food chain					
Microorganisms in sewage treatment					
soil (agricultural)					
Air					

## **Chemical Name:**

Benzyl alcohol

**EC No.: CAS-No.:** 202-859-9 100-51-6

# **DNELs - Derived no effect level**

	Workers			Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral		Not i	required			20 mg/kg bw/d		4 mg/kg bw/d
Inhalation	-	110 mg/m <sup>3</sup>	-	22 mg/m³	-	27 mg/m³	-	5.4 mg/m <sup>3</sup>
Dermal	-	40 mg/kg bw/d	-	8 mg/kg bw/d	-	20 mg/kg bw/d	-	4 mg/kg bw/d

## PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	1 mg/l
Fresh water sediments	5.27 mg/kg
Marine water	0.1 mg/l
Marine sediments	0.527 mg/kg
Food chain	
Microorganisms in sewage treatment	39 mg/l
soil (agricultural)	0.456 mg/kg
Air	

**Chemical Name:** 

Formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane and phenol

**EC No.: CAS-No.:** 500-006-8 9003-36-5

#### DNELs - Derived no effect level

	Workers			Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							6.25 mg/kg bw/d
Inhalation				29.39 mg/m <sup>3</sup>				8.7 mg/m <sup>3</sup>
Dermal				104.15 mg/kg				62.5 mg/kg bw/d
	_			bw/d				

# PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.003 mg/l
Fresh water sediments	0.294 mg/kg
Marine water	0.0003 mg/l
Marine sediments	0.0294 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/l
soil (agricultural)	0.237 mg/kg
Air	

#### 8.2 Exposure controls

9.1

# **Personal Protection**

**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment, filter A.

EYE PROTECTION: Eye wash bottle with pure water. Safety glasses with side-shields conforming to EN 166.

**HAND PROTECTION:** Protective gloves complying with EN 374: Nitrile rubber. Butyl rubber. PVA. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Ensure adequate ventilation, especially in confined areas.

# **SECTION 9: Physical and Chemical Properties**

Information on basic physical and chemical properties Colour: clear				
Physical State	Liquid			
Odor	slight			
Odor threshold	Not determined			
рН	8			
Melting point / freezing point (°C)	Not determined			
Boiling point or initial boiling point and boiling range (°C)	201 - N.D.			
Flash Point, (°C)	Not measured			
Evaporation rate	Not determined			
Flammability (solid, gas)	Not determined			
Llower and upper explosive limit	Not determined			
Vapour Pressure	Not determined			
Relative vapour density	Not determined			

Density and/or relative density ca. 1.1 g/cm<sup>3</sup>

Solubility in / Miscibility with water slight

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Not determined

Not determined

Not determined

Particle characteristics Not applicable to liquids

9.2 Other information

VOC Content g/l: <30

Specific Gravity (g/cm3) 0.120

# **SECTION 10: Stability and Reactivity**

#### 10.1 Reactivity

No reactivity hazards known under recommended storage and use conditions.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Amines cause exothermic reactions.

#### 10.4 Conditions to avoid

Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Do not freeze.

#### 10.5 Incompatible materials

Oxidizing agents. Acids and bases.

## 10.6 Hazardous decomposition products

In case of fire **hazardous decomposition products** may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as definied in Regulation (EC) No 1272/2008

**Acute Toxicity:** 

Oral LD50: No Information Inhalation LC50: No Information Dermal LD50: No Information

Irritation: Irritating to eyes and skin.

Corrosivity: No information available.

Sensitization: Prolonged or repeated skin contact may result in allergic eczema.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

Date Printed: 12/04/2023 Product: FLOWSEAL EPW GLOSSY PART A

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
25068-38-6	Reaction product: bisphenol- A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	>5000 mg/kg (rat)	2001 mg/kg (rat) OECD 402	>20 mg/l	0.000	>5 mg/l
16096-31-4	1,6-Hexanediol diglycidyl ether	3010 mg/kg (rat)	>2000 mg/kg (rat)		0.000	0.000
108-32-7	Propylene carbonate	33520 mg/kg (rat)	>2000 (rabbit)		0.000	
100-51-6	Benzyl alcohol	1620 mg/kg (rat)	2001 mg/kg (rabbit)			> 4.178 mg/l (4 h, rat)
9003-36-5	Formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane and phenol	>5000 mg/kg (rat) OECD 401	>2000 mg/kg (rat) OECD 402		0.000	0.000

#### **Additional Information:**

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Ingestion may cause irritation to mucous membranes. Irritating to eyes and skin. May cause allergic skin reaction.

# 11.2 Information on other hazards

**Endocrine disrupting properties - Toxicity** 

Name According to EEC CAS-No.

No Information

# **SECTION 12: Ecological Information**

# 12.1 Toxicity:

EC50 48hr (Daphnia):No informationIC50 72hr (Algae):No informationLC50 96hr (fish):No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

## 12.6 Endocrine disrupting properties

**Endocrine disrupting properties - Ecotoxicity** 

Name According to EEC CAS-No.

Product: FLOWSEAL EPW GLOSSY PART A

Date Printed: 12/04/2023

No Information

#### 12.7 Other adverse effects:

#### No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
1675-54-3	bis[4-(2,3-epoxypropoxy)phenyl]propane	No information	No information	1.3 mg/l
25068-38-6	Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	1.7 mg/l OECD 202	13.81 mg/l (Pseudokirchneriella subcapitata) OECD 201	1.5 mg/l (Oncorhynchus mykiss) OECD 203
16096-31-4	1,6-Hexanediol diglycidyl ether	47 mg/l	No information	30 mg/l
108-32-7	Propylene carbonate	No information	No information	>1000 mg/l
100-51-6	Benzyl alcohol	230 mg/l	770 mg/l (Pseudokirchneriella)	460 mg/l (Pimephales promelas)
9003-36-5	Formaldehyde, oligomeric reaction product with 1-chloro-2,3-epoxypropane and phenol	1.6 mg/l	1.8 mg/l (Pseudokirchnerella subcapitata) OECD 201	0.55 mg/l

# **SECTION 13: Disposal Considerations**

13.1 WASTE TREATMENT METHODS: Dispose of waste material at an approved hazardous waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems. Contaminated packaging to be disposed of as product. Fully drained containers which are drop- and scrape-free can be treated as industrial waste, and can possibly be recycled. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

**European Waste Code:** 080119\* Packaging Waste Code: 150110

# **SECTION 14: Transport Information**

Date Printed: 12/04/2023

		ADR/RID	ADN	IMDG	IATA
14.1	UN-number or ID number	UN3082	UN3082	UN3082	UN3082
14.2	UN proper shipping name	Environmentally hazardous substance, liquid, N.O.S.,(Epoxy Resin MW<700)	Environmentally hazardous substance, liquid, N.O.S.,(Epoxy Resin MW<700)	Environmentally hazardous substance, liquid, N.O.S.,(Epoxy Resin MW<700)	Environmentally hazardous substance, liquid, N.O.S., (Epoxy Resin MW<700)
14.3	Transport Hazard Class(es)	9	9	9	9
14.4	Packing Group	III	III	III	III
14.5	Enviromental Hazards	No Information	No Information	No Information	No Information

14.6 Special precautions for user Not applicable EmS-No.: F-A, S-B

14.7 Maritime transport in bulk according to IMO

intruments

Not applicable

# **SECTION 15: Regulatory Information**

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

**National Regulations:** 

**Denmark Product Registration Number:** PR-nr. 894199

Danish MAL Code: 0-3 (1993)

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

**Norway Product Registration Number:** Not available

Germany WGK Class: Not available

Directive 2004/42/CE: <30

Not applicable Covered by Directive 2012/18/EC (Seveso III):

Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:

Not applicable

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# SECTION 16: Other Information

## Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Reasons for revision

•

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

#### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu$ m.

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.